

TAMPODIEL®

Recommended Applications:

Pieces of PVC, ABS, SAN,
Polycarbonates,
Metacrylates,
Treated polyesters, etc.

SERIES

35

One component ink developed for pad-printing on pieces of materials as basic as PVC, ABS, SAN, polycarbonates, metacrylates, treated polyesters, etc.

35 SERIES leaves a thin, hard and well adhered film in all these materials, and has a high chemical resistance. 35 SERIES has a good equilibrium between the wetting of the pad and the releasing from it onto the substrate. It leaves no residual odour.

Recommended applications: Pieces of PVC, ABS, SAN, polycarbonates, metacrylates, treated polyesters, etc.

Finish: Gloss.

Presentation: Only viscosity needs to be adjusted, depending on the job, factory temperature and impression speed.

Diluents: D-200 as fast to normal and D-696 as slow. Its adequate mixture gives a good behaviour in the ink duct and short drying times when dried at ambient temperature, depending on the material and the job. When it passes through a tunnel, it dries in seconds.

Colours: See table COLOURS/SERIES.

Any other colour can be formulated on demand.

The information supplied is a result of our updated knowledge; it is supplied with good intention but under no circumstances it can be taken as a guarantee. Moreover, taking into account the great diversity of printable materials, the diversity of machinery and procedures to carry out the jobs, it is the user's responsibility to check the suitability of our products to obtain the objectives he desires, with the resources and procedures he has. The user must also be make sure he complies with the current legislation, situation of patents and third party rights when applicable.

Autovía Fuenlabrada-Pinto Km 15,200 28940 FUENLABRADA (MADRID) - SPAIN
Tfn: +34 916 421 789 Fax: +34 916 421 834 e-mail: sales@argadiel.com
ES-A-28635514

FT/M/03/ING

AFFORD INDUSTRIAL, S.A.